

规格型号 SPEC NO.	UL1007 20AWG	参照标准 REFERENCE STANDARD	UL1581 / UL758
额定温度 RATED TEMPERATURE	80℃	额定电压 RATED VOLTAGE	300V
阻燃等级 FLAME RETARDANT GRADE	VW-1	环保标准 ENVIRONMENTAL STANDARDS	RoHS

结构项目 CONSTRUCTION ITEM

导体 CONDUCTOR	构造规格 SECTIONAL AREA	AWG/ mm	21/0.178±0.008TS
	导体材质 MATERIAL	镀锡铜丝
	截面积 SECTIONAL AREA	mm ²	0.52
	绞合外径 STRANDED DIAMETER	mm	0.94
绝缘 INSULATION	材质 MATERIAL	PVC
	平均厚度 THE AVERAGE THICKNESS	mm	0.43
	最小厚度 MINIMUM GAUGE	mm	0.39
	颜色 COLOR	黑、红、黄、白、兰、绿、紫、灰、橙、棕、黄注绿
	绝缘外径 INSULATION DIAMETER	mm	1.8±0.1
屏蔽隔离 SHIELDING	包带 COVERING	/
	屏蔽方式 SCREEN MODE	/
	构造规格 SECTIONAL AREA	AWG/ mm	/
	屏蔽材质 MATERIAL	/
	绞合总外径 TOTAL DIAMETER	mm	/
外被 JACKET	材质 MATERIAL	/
	平均厚度 THE AVERAGE THICKNESS	mm	/
	最小厚度 MINIMUM GAUGE	mm	/
	颜色 COLOR	/
	线材外径 OVERALL DIAMETER	mm	/

印字内容 PRINTING CONTENT

E249743  AWM 1007 20AWG 80℃ 300V VW-1 CHENGXING
 AWM IA 20AWG 80℃ 300V FT1

结构简图 STRUCTURE DIAGRAM

绝缘 INSULATION

导体 CONDUCTOR

绝缘 INSULATION

